


ND-APG0421HV
One Switch Endless Surveillance Power



Product Description

A Compact PoE+ Switch Delivering a Total PoE Power 65W and up to 30W Per Port. Ideal For Powering IP Cameras And Network Devices With Smart Priority Power Protection to Ensure Stable Performance



Follow us :



Function Characteristic:

- ★ 4*10/100/1000Mbps PoE ports, 2*10/100/1000Mbps uplink port, 1*1000Mbps SFP Slot
- ★ Support IEEE 802.3af/at.
- ★ Support Restrain Network Storm, VLAN Function.
- ★ Support Max Transmission up to 250m with PoE Power.
- ★ All Ports Supported by MDI/MDIX Auto Flip and Self Negotitation.
- ★ In-Built Power Supply.
- ★ Maximum Power of Single PoE Port: 30W
- ★ Maximum PoE Power: 65W
- ★ Adopts Store-and Forward Architecture.
- ★ Fanless, Natural Cooling, Small, Compact and Quiet Design Suitable For Desktop or Wall.
- ★ Support Watchdog Function.
- ★ Support Lightning Protection 6KV.





Specifications :

MODEL	ND-APG0421HV		
Power	Power Adapter Voltage	AC 110V-240V	
	Consumption	65W (52V 1.44A)	
Network Connector	Network Port	PoE Ethernet Port	1-4 Port: 10/100/1000Mbps
		Ethernet Port	Uplink Port: 10/100/1000 Mbps
		Watchdog	1-4 Port
		SFP Port	SFP Port:1000Mbps
	Transmission Distance	1-4 Port: 100Mbps 0-100m; 10mbps: 0-250m; Uplink Port: 0-100m SFP depends on the optical module(20km..100km)	
	Transmission Medium	Cat5/5e/6 Standard Network Cable	
Network Switch	Network Standard	IEEE 802.3/802.3u, IEEE 802.3x, IEEE 802.ab,	
	Switching Capacity	14Gbps	
	Packet Buffer Memory	2Mbits	
	Throughput	10.416Mpps	
	MAC Table	2K	
Power Over Ethernet	Packet Forwarding rate	10Mbps:14880pps/port 100Mbps:148800pps/port 1000Mbps:1488000pps/port	
	PoE Standard	IEEE 802.3af/at	
	PoE Power Supply	12 +,36-;4578-,8 cores Power Supply	
RJ45 Port	PoE Power	af=15.4w.at=30w for each port	
	Port Function	Power Priority mechanism, fast and forward MAC automatic learning and aging IEEE 802.3X full duplex and mode and back- pressure for half - duplex mode	
	Watchdog function	When Camera stops Working 2mins,the port will restart and recover automatically the camera	
LED Indicator	LED Indicator	LINK/ACT.100Mbps: PoE Status Indicator Power indicator; Extender	
Environmental	Working Temperature	0°C~55°C	
	Relative Humidity	20~95%	
	Storage Temperature	-20°C~70°C	



Follow us :



Mechanical	Dimension (LxWxH)	190mm*125mm*38mm
	Relative Humidity	Black
	Storage Temperature	0.76kg

Application:

